

LED Disk Light



BL-DSKL7.5-15YYZZ

Driver Info

Type:	Constant Current
120V:	Yes
277V:	N/A
480V:	N/A
Input Watts:	15W
Efficiency:	88%

LED Info

Watts:	15W
Color Temp:	5000K
Color Accuracy:	90CRI
L70 Lifespan:	50000
Lumens:	1050
Efficacy:	70LPW

Provides maintenance-free illumination for outdoor use in residential and commercial applications such as retail, education, multi-unit housing and storage. Ideal for lighting building facades, parking areas, walkways, garages, loading areas and any other outdoor space requiring reliable safety and security.

Color: White

Weight: 0.66lbs(0.3Kg)



Technical Specifications

Listings

ETL Listing:

Damp locations.
ETL code: 4007551

IESNA LM-79 & IESNA LM-80 Testing:

This product has been tested by an independent laboratory in accordance with IESNA LM-79 and 80, and have received the Department of Energy "Lighting Facts" label.

Electrical

DOB Driver

Constant Current, 120 V, 50-60Hz

THD:

<15%

Power Factor:

>0.9

LED Characteristics

Lifespan:

50,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations.

LEDs:

Discreet LEDs on PCB board

Color Uniformity

CCT(Correlated Color Temperature) follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting(SSL) Products, ANSI C78.377-2015.

Construction

Cold Weather Starting:

Minimum starting temperature is -40°F(-40°C)

Ambient Temperature

Suitable for use in 104°F(40°C) ambient Temperatures.

Housing:

Steel

Lens:

Vandal-resistant polycarbonate textured opaque for low glare flat lens

Mounting:

Ceiling mount to recessed junction with knockout template or directly to ceiling surface, utilizing side conduit entry points.

Finish:

Our environmentally friendly polyester powder coatings are formulated for high-durability and long-lasting color, and contain no VOC or toxic heavy metals.

Green Technology:

Mercury and UV free RoHS compliant components Polyester powder coat finish formulated without the use of VOC or toxic heavy metals.

Other

3 Yr Limited Warranty:

Fixture operation and paint finish are covered for a period of 3 years.

Accessories options:

Fits the footprint of older canopy lights
Vandal resistant and UV resistant lens
Ultra-high efficiency
Clean, contemporary, low-profile design
Easy installation, fitting all different kinds of junction box

Order Information


BL — DSKL — Size — Wattage — YYZZ

BL — DSKL — 7.5" — 15W


BL — DSKL — 7.5 — 15 — YYZZ

LED Disk Light



Lux Chart/Photometrics



Height	Average Lux (lx)	Light range (dia.)
1M	392	284.96cm
2M	98	569.92cm
3M	43.55	854.88cm
4M	24.5	1139.84cm
5M	15.68	1424.79cm



Compatible j-box and can sizes



Reccssed



Retrofit Kit

