

LED Wall Sconce

Specification

Introduction:




This wall sconce can be used indoor and outdoor both, beautiful and silicone rubber waterproof seal, internal epoxy potting, ensuring superior waterproof lamps performance. High-brightness light source of imported chips, high brightness, low power, low heat, long life reaches 50000H, can be divided into color, colorful discoloration. It is mostly for decoration and sometimes it can be also for lighting. The lamps are sealed extrusion and molded power connections make it resistant to water, dirt and any weather conditions. Consumes up to 15% less energy than traditional one and will quickly pay for itself. Also it is easy to install and anyone can do it, no training or special tools required. Quick mount installation brackets and channels are available for applications.



Features and advantage:

- 1) Can be in different cover color;
- 2) Wide input voltage from AC 100V to AC 277V;
- 3) Easy base fixture for installation;
- 4) LED 3000K, 4000K, 5000K, 6000K in option;
- 5) With high brightness 2835 SMD LED chip;
- 6) ETL, cETL, CE, RoHS approval;
- 7) Black cover and white cover in option;
- 8) IP65 waterproof. Both indoor and outdoor use;
- 9) Special appearance design.

Technical Parameters:

Model	Size(MM)	Power (W)	Photo	Input voltage	Cover color	LED color	Shell material	Working temperature	Base	PF	IP
PL-LB-R-20W-A	Φ230*H80	20W		AC100-277V	White	5000K	Plastic+aluminum PCB	-20 ~45℃	J-box	0.9	65
PL-LB-O-20W-A	L270*W145*H74	20W		AC100-277V	White	5000K	Plastic+aluminum PCB	-20 ~45℃	J-box	0.9	65
PL-LB-S-20W-A	L220*W180*H74	20W		AC100-277V	Black	5000K	Plastic+aluminum PCB	-20 ~45℃	J-box	0.9	65

Application:

1) Hotel; 2) Motel; 3) Building; 4) House; 5) Garden lighting; 6) Column; 7) Area lighting

Warning:

- To prevent personal injury or product damage only licensed electricians should install.
- To avoid electric shock or component damage disconnect power before attempting installation or servicing.
- This product must be installed in accordance with the national electric code (NEC) and all applicable federal, state and local electric codes and safety standards.
- Any alteration or modification of this product is expressly forbidden as it may cause serious personal injury, death, property damage and/or product malfunction.
- To prevent product malfunction and/or electrical shock this product must be properly grounded.
- This luminaire is designed to operate in ambient temperatures ranging from -20°C to 45°C.