

DESCRIPTION

Ultra slim design, lamp thickness only 0.39".

Features color tunable technology lets the user choose between 2700K, 3000K, 3500K 4000K, or 5000K.

Easy Installation, no housing needed.

Wet-location rated, ideal for bathrooms, laundry, porches and garage work rooms



BASED ON SAMPLE SETTING.ACTUAL LUMENS MAY VARY

MODEL#	SIZE	WATTAGE	5CCT	LUMENS
KOK-4EJCT09SR05	4inch	9W	2700K 3000K 3500K 4000K 5000K	562Lm 613Lm 637Lm 644Lm 602Lm

. SPECIFICATION	TECHNICA
120V	VOLTAGE
60Hz	POWER FREQUENCY
>0.9	POWER FACTOR
2700K 3000K 3500K 4000K 5000K	5CCT
90	CRI
120°	BEAM ANGLE
PS+AL	MATERIAL
≥50,000hours	LIFESPAN
(-4°F~ 113°F) -20~45°C	OPERATING TEMP
Triac Dimming	DIMMABLE
Suitable for Wet Locations	RATING
5 year limited	WARRANTY

FEATURES

- Edge-lit technology, with no glare or dark spots
- Continuous dimming from 100% to 10% with many Triac Dimmers
- Instant on
- No flicker
- •Color removable trim available (sold separately): Brushed nickel, Black, Bronze

INSTALLATION

No existing recessed housing or junction box required. Suitable for most new constructions. Install J-Box in ceiling beam, and insert light right into drywall opening.

DIMMING

Compatible with most triac dimmers to give user a smooth 100%-10% dimming to choose the desired brightness. Please check the recommended dimmer list in next page.

ELECTRICAL

This fixture is built with the highest quality 120V drivers, ensuring energy efficiency.

ENERGY SAVINGS

80% more energy savings than halogen lamps.




LISTING

ETL Listed. Energy Star. Title24.





DIMENSION



RECOMMENDED DIMMER

LUTRON				LEVITON
TG-600PR-WH	TGCL-153PH-LA	SCL-153PH-WH	MSCL-0P153M	6672
S-600PR-WH	SLV-600P-AL	GT-600P	MACL-153M//MA-R	6674 RNL06
CTCL-153PDH-WH	DV-600PR-WH	DVCL-153P	PD-6WCL	DSL06 IPL06



