

Round Slim Panel Series IV

5CCT Baffle Bound Slim Panel

Date: Catalog Number: Project Name: Note: Type:



BASED ON SAMPLE SETTING.ACTUAL LUMENS MAY VARY.				
MODEL#	SIZE	WATTAGE	5CCT	LUMENS
4EJCT09SR05-B	4inch	9W	2700K 3000K 3500K 4000K 5000K	619Lm 665Lm 699Lm 701Lm 661Lm
MODEL#	SIZE	WATTAGE	5CCT	LUMENS
6EJCT12SR05-B	6inch	12W	2700K 3000K 3500K 4000K 5000K	957Lm 990Lm 999Lm 1010Lm 952Lm

DASED ON SAMPLI	E SEI III	IG.ACTUAL I	LUMENS IV	IAT VART.
MODEL#	SIZE	WATTAGE	5CCT	LUMENS
4EJCT09SR05-B	4inch	9W	2700K 3000K 3500K 4000K 5000K	619Lm 665Lm 699Lm 701Lm 661Lm
MODEL#	SIZE	WATTAGE	5CCT	LUMENS
6EJCT12SR05-B	6inch	12W	2700K 3000K 3500K 4000K	957Lm 990Lm 999Lm 1010Lm

TECHNICAL SPECIFICATION		
VOLTAGE	120V	
POWER FREQUENCY	60Hz	
POWER FACTOR	>0.9	
5CCT	2700K 3000K 3500K 4000K 5000K	
CRI	90	
BEAM ANGLE	100°	
MATERIAL	PS+AL	
LIFESPAN	≥50,000hours	
OPERATING TEMP	(-4°F~ 113°F) -20~45°C	
DIMMABLE	Triac Dimming	
RATING	Suitable for Wet Locations	
WARRANTY	5 year limited	













FEATURES

- · Baffle trim design
- Edge-lit technology, with no glare or dark spots
- Continuous dimming from 100% to 10% with many Triac Dimmers
- Instant on
- No flicker

INSTALLATION

No existing recessed housing or junction box required. Suitable for most new constructions.

Install J-Box in ceiling beam, and insert light right into drywall opening.

DIMMING

Compatible with most triac dimmers to give user a smooth 100%-10% dimming to choose the desired brightness.

Please check the recommended dimmer list in next page.

ELECTRICAL

This fixture is built with the highest quality 120V drivers, ensuring energy efficiency.

ENERGY SAVINGS

80% more energy savings than halogen lamps.

LISTING

ETL Listed. Energy Star. Title 24.



Round Slim Panel Series IV

5CCT Baffle Round Slim Panel

Catalog Number: Project Name: Note: Date: Type:

4inch & 6inch: Easily flip the switch for desired CCT





Products view

SIZE & DIMENSION & HOLE CUTOUT

Size	Dimension	
4inch	04.92(1254.05mm) 1.227(314.1mm)	Ф4 21/64"(110mm)
6inch	4.23.(1754.15mm) 1.227(31±0.5mm) 1.34(34.1mm)	Φ6 19/64"(160mm)

RECOMMENDED DIMMER

	LUTRO	N		LEVITON
TG-600PR-WH	TGCL-153PH-LA	SCL-153PH-WH	MSCL-0P153M	6672 RNL06
S-600PR-WH	SLV-600P-AL	GT-600P	MACL-153M//MA-R	6674 IPL06
CTCL-153PDH-WH	DV-600PR-WH	DVCL-153P	PD-6WCL	DSL06

ACCESSORIES







Connector