

## **Spotlight Series**

Architectural Multi-head Recessed Spot Downlight

Catalog Number:

Project Name:

Note:

Date:

Type:

### DESCRIPTION

Adopt integrated design, unique Aluminum heat dissipation structure, improve heat dissipation efficiency effectively prolong service life.

Built-in COB chip, good color display and high brightness

With adjustable colors, 360° rotation, 20° tilt, and narrow beam angles of 15°, 24°, 38° to highlight architectural or artistic elements in your home.

Ideal for boLiving room, bedroom, kitchen, washroom, school, university, hospital, hotel, conference, meeting room, show room, showcase;



TECHNICAL SPECIFICATION				
VOLTAGE	120V			
POWER FREQUENCY	60Hz			
POWER FACTOR	>0.9			
ССТ	2700K 3000K 3500K  4000K  5000K			
CRI	90			
BEAM ANGLE	15°/24°/38°			
MATERIAL	AL+lens			
LIFESPAN	≥50,000hours			
OPERATING TEMP	(-4°F~ 113°F) -20~45°C			
DIMMING	Triac Dimming			
RATING	Suitable for Wet Locations			
WARRANTY	5 year limited			



### FEATURES

- · Professional optical lens, uniform light
- · Powder coated surface treatment is durable and not easy to fall off
- Excellent aluminum reflector offers even and better light color, bringing visual comfort
- Tilting gimbal light source for directional lighting

#### INSTALLATION

No existing recessed housing or junction box required. Suitable for most new constructions. Install J-Box in ceiling beam, and insert light right into drywall opening.

#### DIMMING

Compatible with most triac dimmers to give user a smooth 100%-10% dimming to choose the desired brightness. Please check the recommended dimmer list in next page.

#### ELECTRICAL

This fixture is built with the highest quality 120V drivers, ensuring energy efficiency.

#### **ENERGY SAVINGS**

80% more energy savings than halogen lamps.

#### LISTING


ETL Listed.



# **Spotlight Series**

Architectural Multi-head Recessed Spot Downlight

Catalog Number :	Project Name:	Note:	Date:	Туре:
360º Rotation		20º Tilt Range	Narrow light	angle optional: 15°,24°, 38°
		6		
Finishing section trims are durable di with precision painted finish.	e cast aluminum		thermal management maintenance.	ovide optimized passive to maximize LED lumen ard) provides long useful
Square reflec	stor	Rotating bracket The precise rotating		color control over time. ting surface ring, allowing the lamp



#### **RECOMMENDED DIMMER**

LUTRON				LEVITON
CTCL-153PDH-WH TGCL-153PH-LA SLV-600P-AL	DVCL-153P MSCL-0P153M PD-6WCL	CT-103PR-WH MACL-153MA RCL-153RNL	DVRF-6L CTCL-150H	RNL06 DSL06