



# Round Slim Panel Series

## Fire Rated LED Round Slim Panel

Catalog Number : Project Name : Note : Date : Type :

### DESCRIPTION

Fire-Rated Downlights, fixtures are code compliant for use in fire-rated constructions for up to a maximum of 2 hours.

Features color tunable technology lets the user choose between 2700K, 3000K, 3500K, 4000K, or 5000K.

Wet-location rated, ideal for bathrooms, laundry, porches and garage work rooms.

Available size: 4", 6"



4"



6"



BASED ON SAMPLE SETTING. ACTUAL LUMENS MAY VARY.

MODEL	SIZE	WATTAGE	LUMENS
4EJCT09SR05-FR	4inch	9W	630Lm

MODEL	SIZE	WATTAGE	LUMENS
6EJCT12SR05-FR	6inch	12W	960Lm

### TECHNICAL SPECIFICATION

VOLTAGE	<b>120V</b>
POWER FREQUENCY	<b>60Hz</b>
POWER FACTOR	<b>&gt;0.9</b>
5CCT	<b>2700K   3000K   3500K   4000K   5000K</b>
CRI	<b>90</b>
BEAM ANGLE	<b>120°</b>
MATERIAL	<b>Aluminum+steel casing</b>
LIFESPAN	<b>≥50,000hours</b>
OPERATING TEMP	<b>(-4°F~ 113°F) -20~45°C</b>
DIMMABLE	<b>Triac Dimming</b>
RATING	<b>Suitable for Wet Locations</b>
WARRANTY	<b>5 year limited</b>

### FEATURES

- 2-Hour fire rating
- Edge-lit technology, with no glare or dark spots
- Instant on
- No flicker

### INSTALLATION

No existing recessed housing or junction box required.

Suitable for most new constructions.

Install J-Box in ceiling beam, and insert light right into drywall opening.

### DIMMING

Compatible with most triac dimmers to give user a smooth 100%-10% dimming to choose the desired brightness.

Please check the recommended dimmer list in next page.

### ELECTRICAL

This fixture is built with the highest quality 120V drivers, ensuring energy efficiency.

### ENERGY SAVINGS

80% more energy savings than halogen lamps.

### LISTING

ETL Listed.



Specification subject to change without notice



# Round Slim Panel Series

## Fire Rated LED Round Slim Panel

Catalog Number:      Project Name:      Note:      Date:      Type:

4inch&6inch: Easily flip the switch for desired CCT

Products view



### SIZE & DIMENSION & HOLE SIZE

SIZE	DIMENSION		HOLE SIZE
4inch			Φ4 21/64"(110mm)
6inch			Φ6 19/64"(160mm)

### RECOMMENDED DIMMER

LUTRON				LEVITON	
TG-600PR-WH	TGCL-153PH-LA	SCL-153PH-WH	MSCL-OP153M	6672	
S-600PR-WH	SLV-600P-AL	GT-600P	MACL-153M//MA-R	6674	RNL06
CTCL-153PDH-WH	DV-600PR-WH	DVCL-153P	PD-6WCL	DSL06	IPL06


### ACCESSORIES



J-Box driver



Connector



Hole cutout card

Specification subject to change without notice