

# Dom Top Round LED Bollard Light

Power 14W/19W/24W | CCT 3000K/4000K/5000K | Lumens 1,800 LM

SKU: BLDTR24W3CCT5KZL

ITEM NO. 181103



## WATTAGE

14W-19W-24W



## INPUT VOLTAGE

AC100-277V



## COLOR TEMPERATURE

3000K, 4000K, 5000K



## LUMEN EFFICACY

75 LM/W



## CRI

>80 Ra



## IP RATING

IP65 (Wet)



## BEAM ANGLE

180°



## LIFESPAN/WARRANTY

50,000 hours/5 years



## FEATURES

- Heavy-duty die-cast aluminum housing with powder-coated finish
- IP65 weather/dust/waterproof rating
- UV-stabilized polycarbonate lens
- Anti-glare optics for reduced glare
- 360° illumination eliminates dark spots

## APPLICATION

- Pathways & Walkways: Guides pedestrians and highlights trip hazards.
- Residential Communities: Enhances curb appeal and security in driveways and common areas.

- Lifespan of 50,000 to 100,000 hours
- Compatible with 120V-277V AC
- Secure mounting with anchor bolts
- On/off photocell for automatic operation

- Commercial & Corporate Campuses: Provides lighting around office entrances and plazas.
- Public Parks & Plazas: Offers ambient lighting for seating areas and walkways.
- Perimeter security: Serves as a visual deterrent and boundary marker.



## SPECIFICATION DATA SHEET

<b>Product Name</b>	Dom Top Round LED Bollard Light
<b>Part Number</b>	BLDTR24W3CCT5KZL
<b>Wattage</b>	14W-19W-24W
<b>Input Voltage</b>	AC100-277V
<b>Frequency</b>	50/60Hz
<b>Color Temperature</b>	3000K, 4000K, 5000K
<b>Dimming</b>	No
<b>CRI</b>	>80
<b>Lumen Efficacy</b>	75 LM/W
<b>Beam Angle</b>	180°
<b>Waterproof Rating</b>	IP65 (Wet)
<b>Housing Material</b>	Aluminum, PC
<b>Housing Color</b>	Bronze, Black
<b>Compliance and Certificates</b>	ETL Listed, RoHS
<b>Lifespan</b>	50,000 hours
<b>Warranty</b>	5 years
<b>Operating Temperature</b>	-40 C ~ +45 C
<b>Operating Humidity</b>	10-65% RH
<b>Storage Temperature</b>	-40 C ~ +45 C
<b>Storage Humidity</b>	10-65% RH
<b>Application</b>	Outdoor
<b>Gross Weight</b>	11 lbs

## CARTON PACKING

<b>Quantity per carton</b>	1
<b>Carton Gross Weight</b>	12 lbs
<b>Carton Size</b>	43.11 x 8.03 x 8.15"

