

## LED WALL PACK

## SLWPQS 12

The brand-new SLWPQS03 series of LED Wall Pack, available only in two size and the power from 30W to 120W, can replace up to 400W MH. Uniform light distribution and excellent LED lumen maintenance rate, high energy efficiency, low cost, while taking into account the stylish design, ensure that the fixture has a long service life. SLWPQS03 also has on-site dimmable output and CCT settings, allowing the contractor to set the lumen value and CCT of the fixture at the installation site to a level that is perfectly suitable for the work site. Emergency egress battery and light control are optional, which is an ideal choice to meet any daily wall-mounted lighting applications.

### Housing

- Rugged die-cast aluminum, corrosion-resistant housing
- Dark bronze polyester powder-coat finish

### LEDs

- LM-80 certified high performance and reliable LEDs

### Electrical

- Universal 120-277V or 120-347V or 347-480 VAC input voltage
- Optional for 0-10V dimming allowing for 10% to 100% dimming
- Operating Temperature Range: -40° C to 40° C (-40° F - + 104° F).
- Optional for CCT and Power adjustable

### Certifications

- ETL Listing
- Wet location

### Warranty


- Five-year warranty.

### Recommended Use

- Pathway
- Building entryways
- Perimeter lighting



**4 Wattage+3CCT**



Size: 14.2 x 9.27 x 4.43 inch

## Accessories



✓		<b>Photocell - Button</b> USE: Photocell is field installed or Pre-installed in factory by requesting	✓		<b>Power and CCT controller</b> USE: The wattage and CCT can be changed by switch selection on the controller.
✓		<b>Emergency Battery Backup</b> USE: It can be pre-installed in factory or field installed	✓		<b>Occupancy Sensor</b> USE: Sensor can be pre-installed in factory or field installed

Model	Wattage	LUMENS	Efficacy	CCT	Certificate
SLWPQS0340NW	40W	5800LM	145LM/W	2700K-6500K	ETL
SLWPQS0360NW	60W	9425LM	145LM/W	2700K-6500K	ETL
SLWPQS0380NW	80W	11600LM	145LM/W	2700K-6500K	ETL
SLWPQS03120NW	120W	17400LM	145LM/W	2700K-6500K	ETL
SLWPQS0380MW-3CCT	80/60/45/30W	4350-11600LM	145LM/W	3000/4000/5000K	ETL
SLWPQS03120MW-3CCT	120/100/80/60W	8700-17400LM	145LM/W	3000/4000/5000K	ETL



+1 281 840 8608  
+1 833 927 2533

5755 Bonhomme Rd #412 Houston, TX 77036  
10004 Gulf Fwy, Houston, TX 77034

www.zaraled.com  
info@zaraled.com